

ASC1202C Two Door Two Way Access Controller



- Support 100,000 valid cards & 150,000 records
- Support multiple cards
- Support card, password, fingerprint and combination
- TCP/IP interface to PC
- Wiegand or RS-485 interface to readers(2 door)
- Anti-pass back, multi-door interlock, multi-card open
- Support 128 efficient time and holiday schedules

ASC1204C-S Four Door Access Controller



- Support 100,000 valid cards & 150,000 records
- Support multiple cards
- Support card, password, fingerprint and combination
- TCP/IP interface to PC
- Wiegand or RS-485 interface to readers(2 door)
- Anti-pass back, multi-door interlock, multi-card open
- Support 128 efficient time and holiday schedules

ASC1204C-D Four Door Two Way Access Controller



- Support 100,000 valid cards & 150,000 records
- Support multiple cards
- Support card, password, fingerprint and combination
- TCP/IP interface to PC
- Wiegand or RS-485 interface to readers(2 door)
- Anti-pass back, multi-door interlock, multi-card open
- Support 128 efficient time and holiday schedules

ASR1100A RFID Reader



- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- Red and Green LEDs
- Watch dog function ensure device free from halting
- Beep Buzzer and LED indicator
- Surface mounted installation

ASR1100B Water-proof RFID Reader



- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- Water-proof design
- Red and Green indicator LEDs
- Watch dog function ensure device free from halting
- Surface mounted installation

ASR1101A RFID Reader



- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- Red and Green LEDs
- Sensitive touch keypad with blue backlight
- Watch dog function ensure device free from halting
- Beep Buzzer and LED indicator
- Surface mounted installation

ASR1101M Vandal-proof RFID Reader



- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- All-metal buttons with blue backlight
- Red and Green indicator LEDs
- Watch dog function ensure device free from halting
- Surface mounted installation

ASR1200D Slim Water-proof RFID Reader



- RS485, Wiegand34/26 protocol
- 13.56MHz(Mifare)
- Red and Blue LEDs
- Watch dog function ensure device free from halting
- Water-proof(Outdoor use)
- Surface/Flush mounted installation

Access Control

ASR1201D

Slim Water-proof RFID Reader + Keypad



- RS485, Wiegand34/26 protocol
- 13.56MHz(Mifare)
- Red and Blue LEDs
- Watch dog function ensure device free from halting
- Water-proof(Outdoor use)
- Surface/Flush mounted installation

ASR1102A(V2)

Fingerprint RFID Reader



- RS-485 protocol
- Default IC (Mifare) card
- Support card, fingerprint
- Up to 3000 fingerprints capacity
- Blue backlight
- Watch dog function ensure device free from halting
- Beep and indicator

ASI1201A

RFID Standalone



- Touch keyboard and LCD display
- Support 30,000 valid cards & 150,000 records
- Support multiple cards(default IC card)
- All-metal buttons with blue backlight
- Support card, password and combination
- Wiegand or RS-485 interface to reader
- TCP/IP to PC

ASI1201E

Water-proof RFID Standalone



- Water-proof design
- Support 30,000 valid cards & 150,000 records
- Support multiple cards(default IC card)
- Support card, password and combination
- Wiegand or RS-485 interface to reader
- Support card, password and combination
- Anti-passback, multi-card open
- TCP/IP to PC

ASI1212D

Water-proof Fingerprint Standalone



- Touch keyboard and LCD display
- Support 30,000 valid cards & 150,000 records
- Support multiple cards(default IC card)
- Support card, password, fingerprint and combination
- Wiegand or RS-485 interface to reader
- Software attendance